

RotoShelf™ FAQ

What are the advantages with RotoShelf™?

- 50-70% reduction in the labour to fill/refill the products in the Multideck case depending on the product.
 - This is verified by tests in various markets; Nordics, Germany, Belgium, USA, South Africa.
- Reduced waste caused by Out-Of-Date
 - Always First-In – First-out helps to reduce waste dramatically
- Increased sales
 - Market feedback shows sales uplift with 7-16%

What products do you recommend using RotoShelf™ for?

- Beverages
- Single pack dairy; milk, yoghurt, cream etc
- Fresh juices
- Basically all products that have short shelf life are suitable

What if the products doesn't glide?

- First action if the products doesn't glide is to check if the surface is dirty or sticky.
- Some products have high friction bottoms and this causes reduced gliding characteristics
- We have our own roller track that goes on the shelf to help with the fronting of difficult products
- We are also working on a pusher so that we can front bagged products and similar goods.

How do I clean the shelves?

- Take the shelf out and wash it off with water and a light detergent
- The shelves have silicone mixed in the plastic and this is not affected by light detergents.

Can RotoShelf™ be installed in any Multideck case?

- No, the RotoShelf™ MD 1250/2 require the below internal dimensions to fit
 - Width: Distance between the back uprights (section width) min: 1200 mm
 - Depth: Min 500mm from the back to the air outlet in top of the case
 - Height: recommended min height is 1600 mm (depending of the products that is in the case)

How is RotoShelf™ installed in the Multideck?

- The standard shelves are taken out and the RotoShelf™ uses the standard uprights in the back of the case.
- Install the top and bottom brackets to the top and bottom base
- Install the top base as high up as possible in the cabinet
- Put the bottom base the correct distance down from the top base.
- Put the frames in between the top and bottom bases
- Start installing the shelves.

Is the RotoShelf™ difficult to install?

No, installing a 1250 mm section takes around 30 min once the standard shelves are taken out of the case. What takes time is setting up the products in the new shelving since a new planogram is required.

How many shelves can you put in RotoShelf™?

Our short 1250/2 frame takes 8 shelves as standard and the long 1250/2 frame takes 10 shelves, however you can fit more but it depends on the products that go on the shelves.

All shelves are adjustable individually and can be spaced tighter together so if you have smaller products you can put additional shelves in a standard case.

Can I use the bottom of the cases as normal?

Yes, but sometimes you can also use our Gravity bottom shelf to get gravity fronting also on the bottom.

How can I do service in a Multideck with RotoShelf™?

Service can always be done through the bottom as normal. The RotoShelf does not sit on the bottom of the Multideck case.

What about service to the RotoShelf™?

We are not using any mechanical parts that need service.

What does the system weigh?

- RotoShelf™ 1250/2: ca 100kg including shelves
- RotoShelf™ 1875/3: ca 150kg
- RotoShelf™ 2500/3: ca 200kg

What is the maximum weight per shelf?

- Universal 70 (used in 1250/2; 1875/3): 40kg
- Universal 90 (used in 2500/3): 76kg
- Beverage 90 (used in 2500/3): 73kg

What warranty do you offer?

We normally give 2 years warranty but this can vary from market to market.